

TASKalfa
552ci

KYOCERA

TASKalfa 552ci | Color Multifunctional System

EVERY DOCUMENT. EVERY TASK. EVERY TIME.





Shown with Optional DSDP, 500 x 2 Tray, and 3,000 Sheet Finisher
50.9" W x 26.8" D x 48.8" H



Shown with Optional DSDP, 500 x 2 Tray, and 1,000 Sheet Finisher
48.8" W x 26.8" D x 48.8" H



Shown with Optional DSDP and 3,000 Sheet LCT
23.8" W x 26.8" D x 48.8" H



Color Touch Screen Control Panel
Screen Dimensions: 8.5" measured diagonally

Hybrid Platform for Advanced Solutions

Basic Specifications

Configuration	Color Multifunctional System - Print/Scan/Copy/Optional Fax
Pages Per Minute	Letter: 55 ppm Black / 50 ppm Color; Legal and Ledger: 28 ppm Black / 25 ppm Color
Warm-up Time	58 Seconds or Less
First Copy Out Time	Black: 4.6 Seconds; Color: 6.1 Seconds
First Print Out Time	Black: 5.2 Seconds; Color: 6.7 Seconds
Resolution / Bit Depth	600 x 600 dpi / 8 Bit Color Depth
Memory / Hard Disk Drive	2 GB RAM / 160 GB x 2 HDDs
Duplex	Standard Stackless, Statement to Ledger, 16 lb Bond - 90 lb Index; 5.5" x 8.5" - 11" x 17"
Electrical Requirements / Weight	120V, 60Hz, 12 Amps / 233 lbs (mainframe only)
Max Monthly Duty Cycle	225,000 Pages Per Month

Paper Supply

Standard Paper Sources	Dual 500 Sheet Trays, 100 Sheet MPT; Auto Selection / Switching, Add Paper While Running
Optional Paper Sources	Dual 500 Sheet Paper Trays PF-720(B) ; 3,000 Sheet Large Capacity Tray PF-760(B)
Paper Capacity	Standard: 1,100 Sheets; Maximum: 4,100 Sheets
Paper Size	5.5" x 8.5" - 11" x 17" (Statement to Ledger)
Paper Weight	Trays: 16 lb Bond - 90 lb Index; MPT: 16 lb Bond - 120 lb Index; PF-760(B) : 16 - 28 lb Bond
Input Materials	Bond Paper, Recycled Paper, Transparencies, Cardstock, Envelopes

Print Specifications

Controller	IBM PowerPC 750 GL / 800 MHz
PDLs/Emulations	PRESCRIBE, PCL6 (5c, XL), KPDL3 (PS3), XPS (Direct Print)
Fonts	136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap
Windows OS Compatibility	Windows 2000 / XP / 2003 / Vista / 2008 / Windows 7
Novell OS Compatibility	Novell NetWare® 3.x/4.x/5.x/6.x
MAC OS Compatibility	Mac OS 10.x
UNIX OS Compatibility	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Interfaces	Standard: 10/100BaseTX, Hi-Speed USB 2.0, USB Host Interface, 2 Expansion Slots
Network Print and Supported Protocols	TCP/IP, IPX/SPX, AppleTalk, NetBEUI, IPv6, IPsec, SSL, WSD Print
Drivers	KX Driver, Mini Driver, KX Driver for XPS, XPS Mini Driver, Network Fax Driver, PPD for MAC
Utilities	PRESCRIBE, PDF Direct Print, KMnet Admin, KMnet for Accounting, KMnet Viewer, Kyocera Command Center

Scan Specifications

Scan Resolutions	200, 300, 400, 600 dpi
File Formats	Black & White: PDF, TIFF; Color: PDF, JPEG, TIFF, XPS
PDF Extension	High Compression PDF, Encrypted PDF
Connectivity / Supported Protocols	10/100BaseTX / TCP/IP
Scanning Functions	Scan to Folder (SMB), Scan to e-Mail, Scan to FTP, Scan to USB, WSD Scan, TWAIN Scan
Driver	TWAIN / WIA Driver

Color and Black & White Scanner

Image Mode	Text, Photo, Text/Photo, Auto, Manual, Map
Continuous Copy	1 - 999 / Auto Reset to 1
Additional Features	Positive/Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, XY Zoom, Job Build, Sheet Insertion
Job Management	Job Interrupt, Job Build, 50 Job Programs, Repeat Copy, 1,000 Department Codes
Color Adjustment	One Touch, Color Balance, Hue, Auto Exposure, Sharpness, Color Calibration, ACS
Magnification / Zoom	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, 25 - 400% in 1 step increments
Document Box	Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

Fax Specifications

Compatibility	G3 Fax
Data Compression	MMR, MR, MH, JBIG
Transmission Speed / Modem Speed	Approximately 3 seconds per page / 33.6 Kbps
Fax Memory	Standard: 12 MB; Maximum: 120 MB
Driver	KM Network Fax Driver
Fax Functions	Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting, Fax Box, Dual Fax

Fax System (S)C / Internet Fax Kit (A) (requires Fax System (S)C)

Optional Document Processors

Type / Capacity	DP-760(B) Dual Scan Document Processor / 100 Sheets DP-750(B) Reversing Automatic Document Processor / 100 Sheets
DSDP Scan Speed DP-760(B)	Simplex: 75 ipm/Duplex: 100 ipm (300 dpi)
RADF Scan Speed DP-750(B)	Simplex: 75 ipm/Duplex: 45 ipm (300 dpi)
Acceptable Originals / Weights	5.5" x 8.5" - 11" x 17", Mixed Size Originals / 9 - 42 lb Bond

DP-760(B) or DP-750(B)

Optional 3,000 Sheet Finisher

Stack / Staple Capacity	Main Tray: 3,000 Sheets; Sub Tray(B): 200 Sheets; Sub Tray(C): 50 Sheets / 50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Paper Size	Main Tray: 8.5" x 11" - 11" x 17"; Sub Tray(B): 5.5" x 8.5" - 11" x 17"; Sub Tray(C): 8.5" x 11"
Paper Weight	Main Tray: 16 lb Bond - 90 lb Index Duplex; 16 lb Bond - 120 lb Index Simplex; Sub Tray (B/C): 16 - 24 lb Bond
Edge Staple Position	3 Positions: Top Left, Bottom Left, Center Bind
Optional Multi-Bin Mailbox	MT-720(B) Includes 7 Trays; Supports 16 lb Bond - 90 lb Index Stack Capacity per Bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"
Optional Punch	PH-5A 2 and 3 Hole Punch Unit, Supports 8.5" x 11" - 11" x 17", 16 lb Bond - 110 lb Index
Optional Saddle Stitch / Fold	BF-720 Supports 8.5" x 11", 8.5" x 14", 11" x 17", 16 lb Bond - 120 lb Index; Over 20 lb Bond Single Sheet Folding Capacity: 1-3 Sheets - 30 Booklets; 4-6 Sheets - 20 Booklets; 7-16 Sheets - 10 Booklets

DF-760(B) (Requires JS-720(B), AK-720)

Optional 1,000 Sheet Finisher

Stack / Staple Capacity	1,000 Sheets; 50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Paper Size / Weight	8.5" x 11" - 11" x 17" / 16 - 28 lb Bond
Edge Staple Position	3 Position: Top Left, Bottom Left, 2 Point Long Edge

DF-780(B) (Requires JS-720(B))

Additional Options

KYOcapture, KYOcapture Express, Equitrac, Fax Memory, Platen Cover Type (E), Job Separator **JS-720(B)**, Attachment Kit **AK-720**, Stand; Data Security Kit (E) Provides Security Overwrite and Encryption for Print, Copy, and Scan; Printed Document Guard Kit (A), Original Hard Copy Holder **DT-710**

Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
© 2010 Kyocera Mita America, Inc.

IC# 855D400256

